



ACC Screwdrivers | Torque range 0.2 – 4.5 Nm

ACC screwdrivers are direct plug-in tools with built-in PCB for automatic cut off and AC to DC rectifier. They are ideal for applications where portability is needed to minimize costly set-up time. ACC models have the unique feature of selectable push to start or push and lever start: to select the working mode just slide the switch located by the start lever.

All ACC models feature shut off torque control through mechanical clutch. It is possible to lock their mechanical clutch and avoid any accidental torque change by adding an optional Lock-out Cover, available for all ACC models (code 219011).



Reverse Switch



Torque Adjusting Nut Cover

Inline ACC Screwdrivers with Built-in Controller

Code	Model	Torque Nm	RPM max	Dimensions mm	Weight kg	Bit Drive
141910	ACC2210	0.2 - 1	950	255 x 35	0.75	Hex 1/4"
141920	ACC2220	0.7 - 2	950	255 x 35	0.80	Hex 1/4"
151222	ACC2222	0.9 - 2	2400	265 x 38	0.85	Hex 1/4"
151930	ACC2230	1.0 - 3	950	265 x 38	0.85	Hex 1/4"
151945	ACC2245	1.0 - 4.5	450	265 x 38	0.85	Hex 1/4"

IMPORTANT: Continuous use over 80% of torque range is not recommended.